




THE DOW CHEMICAL COMPANY MATERIAL SAFETY DATA SHEET



Product Name: UCON(TM) Quenchant RL-XL
MSDS#: 41961

Effective Date: 05/20/2004
Page 1 of 13

Dow (hereinafter, and for purposes of this MSDS only, refers to The Dow Chemical Company and to Dow Chemical Canada Inc.) encourages and expects you to read and understand the entire MSDS, as there is important information throughout the document. Dow expects you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

1.1 IDENTIFICATION

Product Name UCON(TM) Quenchant RL-XL

1.2 COMPANY IDENTIFICATION

The Dow Chemical Company
Midland, MI 48674

1.3 EMERGENCY TELEPHONE NUMBER

24-HOUR EMERGENCY TELEPHONE NUMBER: (989)636-4400.
Customer Information Number: 1-800-258-2436.

MATERIAL SAFETY DATA SHEET

Product Name: UCON(TM) Quenchant RL-XL
MSDS#: 41961

Effective Date: 05/20/2004
Page 2 of 13

2. COMPOSITION INFORMATION

<u>Component</u>	<u>CAS #</u>	<u>Amount (%W/W)</u>
Water	7732-18-5	< 62%
Polyalkylene glycol	Trade secret	< 40%
Corrosion inhibitor	Trade secret	< 4%

3. HAZARDS IDENTIFICATION

3.1 EMERGENCY OVERVIEW

Appearance Transparent pale yellow

Physical State Liquid

Odor Mild

Hazards of product CAUTION!
VAPOR, AEROSOL OR MIST OF THE PRODUCT AND THERMAL DEGRADATION PRODUCTS GENERATED AT HIGH TEMPERATURE CAN BE IRRITATING AND HARMFUL IF INHALED.

3.2 POTENTIAL HEALTH EFFECTS

Effects of Single Acute Overexposure

Inhalation Short-term harmful health effects are not expected from vapor generated at ambient temperature.

Eye Contact May cause mild discomfort.

Skin Contact Prolonged or repeated exposure not likely to cause significant skin irritation.

MATERIAL SAFETY DATA SHEET

Product Name: UCON(TM) Quenchant RL-XL
MSDS#: 41961

Effective Date: 05/20/2004
Page 3 of 13

Skin Absorption Prolonged skin contact is unlikely to result in absorption of harmful amounts.

Swallowing Ingestion may cause gastrointestinal irritation. May cause nausea and vomiting.

Chronic, Prolonged or Repeated Overexposure

Effects of Repeated Overexposure No adverse effects anticipated from available information.

Other Effects of Overexposure Overexposure to vapor, aerosol or mist generated at high temperature may result in eye and respiratory tract irritation, dizziness, nausea and the inhalation of harmful amounts of material.

Medical Conditions Aggravated by Exposure

A knowledge of the available toxicology information and of the physical and chemical properties of the material suggests that overexposure is unlikely to aggravate existing medical conditions.

See Section 11 for toxicological information and additional information about potential health effects.

3.3 POTENTIAL ENVIRONMENTAL EFFECTS

See Section 12 for Ecological Information.

4. FIRST AID PROCEDURES

4.1 INHALATION

Move person to fresh air; if effects occur, consult a physician.

4.2 EYE CONTACT

Flush eyes thoroughly with water for several minutes. Remove contact lenses after the initial 1-2 minutes and continue flushing for several additional minutes. If effects occur, consult a physician, preferably an ophthalmologist.

4.3 SKIN CONTACT

Wash skin with plenty of water.

4.4 SWALLOWING

If patient is fully conscious, give two glasses of water. DO NOT INDUCE VOMITING. Obtain medical attention.

MATERIAL SAFETY DATA SHEET

Product Name: UCON(TM) Quenchant RL-XL
MSDS#: 41961

Effective Date: 05/20/2004
Page 4 of 13

4.5 NOTES TO PHYSICIAN

There is no specific antidote. Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.

5. FIRE FIGHTING MEASURES

5.1 FLAMMABLE PROPERTIES - REFER TO SECTION 9, PHYSICAL AND CHEMICAL PROPERTIES

5.2 EXTINGUISHING MEDIA

Non-flammable (aqueous solution): After water evaporates, remaining material will burn. Use alcohol-type or all-purpose-type foam, applied by manufacturer's recommended techniques for large fires. Use carbon dioxide or dry chemical media for small fires.

5.3 FIRE FIGHTING PROCEDURES

Do not direct a solid stream of water or foam into hot, burning pools; this may cause frothing and increase fire intensity.

5.4 SPECIAL PROTECTIVE EQUIPMENT FOR FIREFIGHTERS

Use self-contained breathing apparatus and protective clothing.

5.5 UNUSUAL FIRE AND EXPLOSION HAZARDS

During a fire, oxides of nitrogen may be produced.

5.6 HAZARDOUS COMBUSTION PRODUCTS

Combustion may produce the following products: Oxides of carbon and nitrogen. See Section 3.2 - Other Effects of Overexposure. Carbon monoxide is highly toxic if inhaled; carbon dioxide in sufficient concentrations can act as an asphyxiant. Acute overexposure to the products of combustion may result in irritation of the respiratory tract. See Section 8.2 - Personal Protection (Ventilation).

6. ACCIDENTAL RELEASE MEASURES

Steps to be Taken if Material is Released or Spilled:

Contain spilled material if possible. See Section 13, Disposal Considerations, for additional information.

Personal Precautions: Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection.

MATERIAL SAFETY DATA SHEET

Product Name: UCON(TM) Quenchant RL-XL
MSDS#: 41961

Effective Date: 05/20/2004
Page 5 of 13

Environmental Precautions: Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

7. HANDLING AND STORAGE

7.1 HANDLING

General Handling

Avoid breathing vapor, aerosol and mist.
Keep container closed.
Use with adequate ventilation.
Wash thoroughly after handling.

See Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION.

Ventilation

Steam and small amounts of organic vapors can be evolved during quenching. The vapors could be irritating and toxic if allowed to accumulate. Adequate workplace ventilation should be provided to prevent irritation and accumulation of vapors; this may require use of a special, local ventilation system in the immediate area where vapors are released.

Other Precautions

Where this product is burned under conditions of relatively complete combustion, the major products are carbon dioxide and water vapor. Where this material is subjected to overheating (thermal degradation) but does not burn, the degradation products can be such things as organic acids (formic, acetic acids), aldehydes, esters, ketones, etc. These vapors or fumes can be highly irritating to the eyes, nose and throat. Special ventilation may be needed. In normal use, no respiratory protective equipment should be needed, but self-contained breathing apparatus should be available for use in emergencies. Small amounts of organic vapor can be formed by oxidation of quenchant. These vapors could be irritating or toxic if released in a poorly ventilated area. Good ventilation should be maintained in the area around quench-tanks.

7.2 STORAGE

Store in the following material(s): 316 stainless steel. carbon steel. glass-lined container. polypropylene. polyethylene lined container. stainless steel. Teflon. This material may soften and lift certain paint and surface coatings. Use product promptly after opening. Store in original unopened container. Shelf life: Use within 2 years. Unopened containers of material stored beyond the recommended shelf life should be retested against the sales specifications before use. Additional storage and handling information on this product may be obtained by calling your Dow sales or customer service contact.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

MATERIAL SAFETY DATA SHEET

Product Name: UCON(TM) Quenchant RL-XL
MSDS#: 41961

Effective Date: 05/20/2004
Page 6 of 13

8.1 EXPOSURE LIMITS

Component	Exposure Limits	Skin. Form
Corrosion inhibitor	5 mg/m3 TWA8 ACGIH	

In the Exposure Limits Chart above, if there is no specific qualifier (i.e., Aerosol) listed in the Form Column for a particular limit, the listed limit includes all airborne forms of the substance that can be inhaled.

A "Yes" in the Skin Column indicates a potential significant contribution to overall exposure by the cutaneous (skin) route, including mucous membranes and the eyes, either by contact with vapors or by direct skin contact with the substance. A "Blank" in the Skin Column indicates that exposure by the cutaneous (skin) route is not a potential significant contributor to overall exposure.

8.2 PERSONAL PROTECTION

Respiratory Protection: None expected to be needed at low temperatures.
See Section 7.1 - Other Precautions.

Ventilation: Steam and small amounts of organic vapors can be evolved during quenching. The vapors could be irritating and toxic if allowed to accumulate. Adequate workplace ventilation should be provided to prevent irritation and accumulation of vapors; this may require use of a special, local ventilation system in the immediate area where vapors are released.

Eye Protection: Safety glasses or monogoggles, as appropriate

Protective Gloves: Use gloves chemically resistant to this material when prolonged or frequently repeated contact could occur.

Other Protective Equipment: Eye Bath, Safety Shower

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Liquid

MATERIAL SAFETY DATA SHEET

Product Name: UCON(TM) Quenchant RL-XL
MSDS#: 41961

Effective Date: 05/20/2004
Page 7 of 13

Appearance: Transparent pale yellow

Odor: Mild

Flash Point - Closed Cup: *Pensky-Martens Closed Cup* None.

Flammable Limits In Air:

Lower *Not Determined, Aqueous System*
Upper *Not Determined, Aqueous System*

Autoignition Temperature: *No test data available.*

Vapor Pressure: 17 mmHg 20 °C

Boiling Point (760 mmHg): 101 °C 214 °F

Vapor Density (air = 1): 1

Specific Gravity (H₂O = 1): 1.068 20 °C / 20 °C

Freezing Point: -6 °C 20 °F

Melting Point: *Not applicable.*

Solubility in Water (by weight): 100 % 20 °C

pH: *Not currently available.*

Evaporation Rate (Butyl Acetate = 1): 1

10. STABILITY AND REACTIVITY

10.1 STABILITY/INSTABILITY Stable.

Incompatible Materials: Normally unreactive; however, avoid strong bases at high temperatures, strong acids, strong oxidizing agents and materials reactive with hydroxyl compounds.

Thermal Decomposition: Where this product is burned under conditions of relatively complete combustion, the major products are carbon dioxide and water vapor. Where this material is subjected to overheating (thermal degradation) but does not burn, the degradation

MATERIAL SAFETY DATA SHEET

Product Name: UCON(TM) Quenchant RL-XL
MSDS#: 41961

Effective Date: 05/20/2004
Page 8 of 13

products can be such things as organic acids (formic, acetic acids), aldehydes, esters, ketones, etc. These vapors or fumes can be highly irritating to the eyes, nose and throat. Special ventilation may be needed. See Section 8.2 - Personal Protection (Ventilation).

10.2 HAZARDOUS POLYMERIZATION Will not occur.

11. TOXICOLOGICAL INFORMATION

Information may be available, call Dow.

12. ECOLOGICAL INFORMATION

12.1 ENVIRONMENTAL FATE

Information may be available, call Dow.

12.2 ECOTOXICITY

Information may be available, call Dow.

12.3 FURTHER INFORMATION

None.

13. DISPOSAL CONSIDERATIONS

13.1 DISPOSAL

MATERIAL SAFETY DATA SHEET

Product Name: UCON(TM) Quenchant RL-XL
MSDS#: 41961

Effective Date: 05/20/2004
Page 9 of 13

DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. DOW HAS NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION 2 (Composition/ Information on Ingredients). FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Incinerator or other thermal destruction device. As a service to its customers, Dow can provide names of information resources to help identify waste management companies and other facilities which recycle, reprocess or manage chemicals or plastics, and that manage used drums. Telephone Dow's Customer Information Group at 1-800-258-2436 or 1-989-832-1556 (U.S.), or 1-800-331-6451 (Canada) for further details .

14. TRANSPORT INFORMATION

14.1 U.S. D.O.T.

NON-BULK

Proper Shipping Name : NOT REGULATED

BULK

Proper Shipping Name : NOT REGULATED

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

15. REGULATORY INFORMATION

15.1 FEDERAL/NATIONAL

OSHA HAZARD COMMUNICATION STANDARD

MATERIAL SAFETY DATA SHEET

Product Name: UCON(TM) Quenchant RL-XL
MSDS#: 41961

Effective Date: 05/20/2004
Page 10 of 13

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 TITLE III (EMERGENCY PLANNING AND COMMUNITY RIGHT-TO-KNOW ACT OF 1986) SECTION 313

To the best of our knowledge this product does not contain chemicals at levels which require reporting under this statute.

SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 TITLE III (EMERGENCY PLANNING AND COMMUNITY RIGHT-TO-KNOW ACT OF 1986) SECTION 302

To the best of our knowledge this product does not contain chemicals at levels which require reporting under this statute.

SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 TITLE III (EMERGENCY PLANNING AND COMMUNITY RIGHT-TO-KNOW ACT OF 1986) SECTIONS 311 AND 312

Delayed (Chronic) Health Hazard : No
Fire Hazard : No
Immediate (Acute) Health Hazard : Yes
Reactive Hazard : No
Sudden Release of Pressure Hazard : No

TOXIC SUBSTANCES CONTROL ACT (TSCA)

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements under 40 CFR 720.30.

EUROPEAN INVENTORY OF EXISTING COMMERCIAL CHEMICAL SUBSTANCES (EINECS)

The components of this product are on the EINECS inventory or are exempt from EINECS inventory requirements.

CEPA - DOMESTIC SUBSTANCES LIST (DSL)

MATERIAL SAFETY DATA SHEET

Product Name: UCON(TM) Quenchant RL-XL
MSDS#: 41961

Effective Date: 05/20/2004
Page 11 of 13

All substances contained in this product are listed on the Canadian Domestic Substances List (DSL) or are not required to be listed.

15.2 STATE/LOCAL

PENNSYLVANIA (WORKER AND COMMUNITY RIGHT-TO-KNOW ACT): PENNSYLVANIA HAZARDOUS SUBSTANCES LIST AND/OR PENNSYLVANIA ENVIRONMENTAL HAZARDOUS SUBSTANCE LIST:

The following product components are cited in the Pennsylvania Hazardous Substance List and/or the Pennsylvania Environmental Substance List, and are present at levels which require reporting.

Component	CAS #	Amount
Corrosion inhibitor	Trade secret	< 4.0000%

PENNSYLVANIA (WORKER AND COMMUNITY RIGHT-TO-KNOW ACT): PENNSYLVANIA SPECIAL HAZARDOUS SUBSTANCES LIST:

To the best of our knowledge this product does not contain chemicals at levels which require reporting under this statute.

CALIFORNIA PROPOSITION 65 (SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT OF 1986)

This product contains no listed substances known to the State of California to cause cancer, birth defects or other reproductive harm, at levels which would require a warning under the statute.

CALIFORNIA SCAQMD RULE 443.1 (SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT RULE 443.1 LABELING OF MATERIALS CONTAINING ORGANIC SOLVENTS)

VOC: Not determined.

This section provides selected regulatory information on this product including its components. This is not intended to include all regulations. It is the responsibility of the user to know and comply with all applicable rules, regulations and laws relating to the product being used.

MATERIAL SAFETY DATA SHEET

Product Name: UCON(TM) Quenchant RL-XL
MSDS#: 41961

Effective Date: 05/20/2004
Page 12 of 13

16. OTHER INFORMATION

16.1 ADDITIONAL INFORMATION

Additional information on this product may be obtained by calling Dow's Customer Information Group at 1-800-258-2436 (U.S.) or 1-800-331-6451 (Canada).

16.2 HAZARD RATING SYSTEM

|| NFPA ratings for this product are: H - 0 F - 0 R - 0

These ratings are part of a specific hazard communication program and should be disregarded where individuals are not trained in the use of this hazard rating system. You should be familiar with the hazard communication programs applicable to your workplace.

16.3 RECOMMENDED USES AND RESTRICTIONS

FOR INDUSTRY USE ONLY

Selection of the appropriate polyglycol product for a specific application requires knowledge of the fluid requirements of the application, awareness of the most important of these requirements, and a match-up with the properties of the various polyglycol materials. Polyglycol products can be formulated for use in numerous industry applications such as hydraulic fluids, quenchant, compressor and refrigeration lubricants, heat transfer fluids, machinery lubricants, solder assist fluids, metalworking lubricants, etc.

Dow recommends that you use this product in a manner consistent with the listed use. If your intended use is not consistent with Dow's stated use, please contact Dow's Customer Information Group at 1-800-258-2436 (U.S.) or 1-800-331-6451 (Canada) for more information.

16.4 REVISION

Version: 2.

Revision: 05/20/2004

Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

MATERIAL SAFETY DATA SHEET

Product Name: UCON(TM) Quenchant RL-XL
MSDS#: 41961

Effective Date: 05/20/2004
Page 13 of 13

16.5 LEGEND

Bacterial/NA	Non Acclimated Bacteria
F	Fire
H	Health
IHG	Industrial Hygiene Guideline
N/A	Not available
NFPA	National Fire Protection Association
O	Oxidizer
R	Reactivity
TS	Trade secret
VOL/VOL	Volume/Volume
W	Water Reactive
W/W	Weight/Weight

NOTICE: Dow urges each customer or recipient of this MSDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this MSDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given., Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that its activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of Dow, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product., Due to the proliferation of sources for information such as manufacturer-specific MSDSs, Dow is not and cannot be responsible for MSDSs obtained from any source other than Dow. If you have obtained a Dow MSDS from a non-Dow source or if you are not sure that a Dow MSDS is current, please contact Dow for the most current version.